



# VISION SYSTEMS

## Service-level agreements

	STANDARD	INTERMEDIATE	ADVANCED	
<b>PERFORMANCE</b>	ACQUISITION SPEED	Up to 200 ppm	Up to 400 ppm	Up to 1,200 ppm
	MAX RESOLUTION	0.2 MP to 48 MP	0.2 MP to 48 MP	0.2 MP to 48 MP
	TRACKING CAPABILITIES	Non-serialized products	Non-serialized and serialized products	Non-serialized and serialized products
	VISION SYSTEM	Up to two cameras*	Up to four cameras*	Unlimited cameras or contact image sensor (CIS)*
<b>AVAILABLE OPTIONS</b>	UPS		24 V	120/240 V
	HMI	15" or 21.5"	15" or 21.5"	15" or 24"
	SERIALIZATION SOFTWARE TOGGLE		•	•
	DATA INTEGRITY	•	•	•
	PC BACK COVER	•	•	•
	REMOTE HMI	•	•	•
<b>TYPICAL INSPECTIONS</b>	LABELING AND PRINTING	•	•	•
	DATA MATRIX PRINTED ON CARTON	•	•	•
	BLISTER		•	•
	COMPONENT PRESENCE		•	•
	OCV AND BARCODE		•	•
	SLAT COUNTER		•	•
	SEAL INTEGRITY		•	•
	ELECTRONIC COUNTER (40 HZ)			•

\* The configuration of the system will depend on the specific requirements of your project and may change after a vision study of the project is performed.